

# Package: phylosem (via r-universe)

November 9, 2024

**Type** Package

**Title** Phylogenetic Structural Equation Model

**Version** 1.1.4

**Date** 2024-04-02

**Imports** sem, ape, phylobase, phylopath, methods

**Depends** TMB, R (>= 4.0.0),

**Suggests** semPlot, TreeTools, Rphylopars, phylolm, fishtree, phyr,  
knitr, rmarkdown, ggplot2, testthat, phylosignal, adephylo

**Enhances** phytools, DiagrammeR

**LinkingTo** RcppEigen, TMB

**Description** Applies phylogenetic comparative methods (PCM) and phylogenetic trait imputation using structural equation models (SEM), extending methods from Thorson et al. (2023) <doi:10.1111/2041-210X.14076>. This implementation includes a minimal set of features, to allow users to easily read all of the documentation and source code. PCM using SEM includes phylogenetic linear models and structural equation models as nested submodels, but also allows imputation of missing values. Features and comparison with other packages are described in Thorson and van der Bijl (2023) <doi:10.1111/jeb.14234>.

**License** GPL-3

**Encoding** UTF-8

**RoxygenNote** 7.3.1

**VignetteBuilder** knitr

**URL** <https://james-thorson-noaa.github.io/phylosem/>

**BugReports** <https://github.com/James-Thorson-NOAA/phylosem/issues>

**Config/pak/sysreqs** cmake libfontconfig1-dev libfreetype6-dev  
libglpk-dev make libicu-dev libxml2-dev libssl-dev

**Repository** <https://james-thorson-noaa.r-universe.dev>

**RemoteUrl** <https://github.com/james-thorson-noaa/phylosem>

**RemoteRef** HEAD

**RemoteSha** 5ac1104dbc4fbd6f05b8f6153ed9335e373f8ea4

## Contents

as_fitted_DAG . . . . .	2
as_phylo4d . . . . .	3
as_sem . . . . .	3
average . . . . .	4
average.compare_phylosem . . . . .	4
best . . . . .	5
best.compare_phylosem . . . . .	5
choice . . . . .	6
choice.compare_phylosem . . . . .	6
coef.phylosem . . . . .	7
compare_phylosem . . . . .	7
list_parameters . . . . .	8
Mlifehist_ver1_0 . . . . .	9
parse_path . . . . .	9
phylosem . . . . .	10
phylosem_control . . . . .	13
print.phylosem . . . . .	14
summary.phylosem . . . . .	15
vcov.phylosem . . . . .	15
<b>Index</b>	<b>16</b>

---

as_fitted_DAG	<i>Convert phylosem to phylopath output</i>
---------------	---

---

### Description

Convert output from package phylosem to phylopath

### Usage

```
as_fitted_DAG(object)
```

### Arguments

object            Output from [phylosem](#)

### Value

Convert output to format supplied by [est\\_DAG](#)

---

as_phylo4d	<i>Convert phylosem to phylo4d</i>
------------	------------------------------------

---

**Description**

Convert output from package phylosem to phylo4d object from package phylobase

**Usage**

```
as_phylo4d(object, what = c("Estimate", "Std. Error"))
```

**Arguments**

object	Output from <a href="#">phylosem</a>
what	Select what to convert (Estimate / Std. Error).

**Details**

This package is intended to for use in using plots associated with package sem, e.g., using package plotSEM `semPlot::semPlotModel`

**Value**

phylosem output to converted format supplied by [phylo4d](#)

---

as_sem	<i>Convert phylosem to sem output</i>
--------	---------------------------------------

---

**Description**

Convert output from package phylosem to output from package sem

**Usage**

```
as_sem(object)
```

**Arguments**

object	Output from <a href="#">phylosem</a>
--------	--------------------------------------

**Value**

Output converted to format supplied by [sem](#)

---

average *Choose model*

---

**Description**

Choose model

**Usage**

```
average(x, cut_off, avg_method)
```

**Arguments**

x	output from compare_phylosem
cut_off	threshold where any model with delta-AIC greater than this value is excluded from average
avg_method	see <a href="#">average_DAGs</a>

**Value**

Returns an AIC-weighted average of fitted models from [compare\\_phylosem](#) after conversion to format from [phylopath::est\_DAG]

---

average.compare\_phylosem  
*Choose model*

---

**Description**

Choose model

**Usage**

```
## S3 method for class 'compare_phylosem'
average(x, cut_off = 2, avg_method = "conditional")
```

**Arguments**

x	output from compare_phylosem
cut_off	threshold where any model with delta-AIC greater than this value is excluded from average
avg_method	see <a href="#">average_DAGs</a>

**Value**

Returns an AIC-weighted average of fitted models from [compare\\_phylosem](#) after conversion to format from [est\\_DAG](#)

---

best	<i>Extract best fitted model</i>
------	----------------------------------

---

**Description**

Extract best fitted model

**Usage**

```
best(x)
```

**Arguments**

x                    output from [compare\\_phylosem](#)

**Value**

Returns best model from those fitted using [compare\\_phylosem](#)

---

best.compare_phylosem	<i>Extract best fitted model</i>
-----------------------	----------------------------------

---

**Description**

Extract best fitted model

**Usage**

```
## S3 method for class 'compare_phylosem'  
best(x)
```

**Arguments**

x                    output from [compare\\_phylosem](#)

**Value**

Returns best model from those fitted using [compare\\_phylosem](#)

choice *Choose model*

---

**Description**

Choose model

**Usage**

```
choice(x, choice)
```

**Arguments**

x                    output from compare\_phylosem  
choice               Integer indicating model to extract

**Value**

Returns chosen model from those fitted using [compare\\_phylosem](#)

---

choice.compare\_phylosem  
*Choose model*

---

**Description**

Choose model

**Usage**

```
## S3 method for class 'compare_phylosem'  
choice(x, choice)
```

**Arguments**

x                    output from compare\_phylosem  
choice               Integer indicating model to extract

**Value**

Returns chosen model from those fitted using [compare\\_phylosem](#)

---

coef.phylosem	<i>Extract path coefficients</i>
---------------	----------------------------------

---

**Description**

Extract path coefficients.

**Usage**

```
## S3 method for class 'phylosem'
coef(object, standardized = FALSE, ...)
```

**Arguments**

object	Output from <a href="#">phylosem</a>
standardized	Whether to standardize regression coefficients
...	Not used

**Value**

Data-frame listing all path coefficients, their parameter index and estimated values

---

compare_phylosem	<i>Compare phylogenetic structural equation models</i>
------------------	--

---

**Description**

Fits several phylogenetic structural equation model for further comparison

**Usage**

```
compare_phylosem(
  sem_set,
  tree,
  data,
  family = rep("fixed", ncol(data)),
  covs,
  estimate_ou = FALSE,
  estimate_lambda = FALSE,
  estimate_kappa = FALSE,
  control = phylosem_control(),
  ...
)
```

**Arguments**

sem_set	A named list of structural equation model specifications, where each element will be passed as argument sem to <a href="#">phylosem</a>
tree	phylogenetic structure, using class <a href="#">as.phylo</a>
data	data-frame providing variables being modeled. Missing values are inputted as NA. If an SEM includes a latent variable (i.e., variable with no available measurements) then it still must be inputted as a column of data with entirely NA values.
family	Character-vector listing the distribution used for each column of data, where each element must be fixed, normal, binomial, or poisson. family="fixed" is default behavior and assumes that a given variable is measured exactly. Other options correspond to different specifications of measurement error.
covs	optional: a character vector of one or more elements, with each element giving a string of variable names, separated by commas. Variances and covariances among all variables in each such string are added to the model. For confirmatory factor analysis models specified via cfa, covs defaults to all of the factors in the model, thus specifying all variances and covariances among these factors. <i>Warning:</i> covs="x1, x2" and covs=c("x1", "x2") are <i>not</i> equivalent: covs="x1, x2" specifies the variance of x1, the variance of x2, <i>and</i> their covariance, while covs=c("x1", "x2") specifies the variance of x1 and the variance of x2 <i>but not</i> their covariance.
estimate_ou	Boolean indicating whether to estimate an autoregressive (Ornstein-Uhlenbeck) process using additional parameter lnalpha, corresponding to the model="OUrandomRoot" parameterization from <b>phylolm</b> as listed in <a href="https://doi.org/10.1093/sysbio/syu005">doi:10.1093/sysbio/syu005</a>
estimate_lambda	Boolean indicating whether to estimate additional branch lengths for phylogenetic tips (a.k.a. the Pagel-lambda term) using additional parameter logitlambda
estimate_kappa	Boolean indicating whether to estimate a nonlinear scaling of branch lengths (a.k.a. the Pagel-kappa term) using additional parameter lnkappa
control	Output from <a href="#">phylosem_control</a> , used to define user settings, and see documentation for that function for details.
...	Additional arguments passed to <a href="#">phylosem</a>

**Value**

An object (list) of class 'compare\_phylosem', containing a list of output from [phylosem](#)

---

list_parameters	<i>List fixed and random effects</i>
-----------------	--------------------------------------

---

**Description**

list\_parameters lists all fixed and random effects



**Usage**

```
list_parameters(Obj, verbose = TRUE)
```

**Arguments**

Obj	Compiled TMB object
verbose	Boolean, whether to print messages to terminal

**Value**

Tagged-list of fixed and random effects, returned invisibly and printed to screen

---

Mlifehist_ver1_0	<i>Fisheries natural mortality example</i>
------------------	--

---

**Description**

Data used to demonstrate phylogenetic comparative methods for fisheries science. Specifically a copy of the Then et al. database [doi:10.1093/icesjms/fsu136](https://doi.org/10.1093/icesjms/fsu136) using file "Mlifehist\_ver1.0.csv" accessed from [https://www.vims.edu/research/departments/fisheries/programs/mort\\_db/](https://www.vims.edu/research/departments/fisheries/programs/mort_db/)

**Usage**

```
data(Mlifehist_ver1_0)
```

---

parse_path	<i>Parse path</i>
------------	-------------------

---

**Description**

parse\_path is copied from sem: :parse.path

**Usage**

```
parse_path(path)
```

**Arguments**

path	text to parse
------	---------------

**Details**

Copied with permission from John Fox under licence GPL ( $\geq 2$ )

**Value**

Tagged-list defining variables and direction for a specified path coefficient

---

 phylosem

*Fit phylogenetic structural equation model*


---

### Description

Fits a phylogenetic structural equation model

### Usage

```

phylosem(
  sem,
  tree,
  data,
  family = rep("fixed", ncol(data)),
  covs = colnames(data),
  estimate_ou = FALSE,
  estimate_lambda = FALSE,
  estimate_kappa = FALSE,
  data_labels = rownames(data),
  tmb_inputs = NULL,
  control = phylosem_control()
)

```

### Arguments

sem	structural equation model structure, passed to either <a href="#">specifyModel</a> or <a href="#">specifyEquations</a> and then parsed to control the set of path coefficients and variance-covariance parameters
tree	phylogenetic structure, using class <a href="#">as.phylo</a>
data	data-frame providing variables being modeled. Missing values are inputted as NA. If an SEM includes a latent variable (i.e., variable with no available measurements) then it still must be inputted as a column of data with entirely NA values.
family	Character-vector listing the distribution used for each column of data, where each element must be fixed, normal, binomial, or poisson. family="fixed" is default behavior and assumes that a given variable is measured exactly. Other options correspond to different specifications of measurement error.
covs	optional: a character vector of one or more elements, with each element giving a string of variable names, separated by commas. Variances and covariances among all variables in each such string are added to the model. For confirmatory factor analysis models specified via <code>cfa</code> , covs defaults to all of the factors in the model, thus specifying all variances and covariances among these factors. <i>Warning</i> : covs="x1, x2" and covs=c("x1", "x2") are <i>not</i> equivalent: covs="x1, x2" specifies the variance of x1, the variance of x2, <i>and</i> their covariance, while covs=c("x1", "x2") specifies the variance of x1 and the variance of x2 <i>but not</i> their covariance.

<code>estimate_ou</code>	Boolean indicating whether to estimate an autoregressive (Ornstein-Uhlenbeck) process using additional parameter <code>lnalpha</code> , corresponding to the <code>model="OUrandomRoot"</code> parameterization from <b>phylolm</b> as listed in <a href="https://doi.org/10.1093/sysbio/syu005">doi:10.1093/sysbio/syu005</a>
<code>estimate_lambda</code>	Boolean indicating whether to estimate additional branch lengths for phylogenetic tips (a.k.a. the Pagel-lambda term) using additional parameter <code>logitlambda</code>
<code>estimate_kappa</code>	Boolean indicating whether to estimate a nonlinear scaling of branch lengths (a.k.a. the Pagel-kappa term) using additional parameter <code>lnkappa</code>
<code>data_labels</code>	For each row of data, listing the corresponding name from <code>tree\$tip.label</code> . Default pulls <code>data_labels</code> from <code>rownames(data)</code>
<code>tmb_inputs</code>	optional tagged list that overrides the default constructor for TMB inputs (use at your own risk)
<code>control</code>	Output from <code>phylosem_control</code> , used to define user settings, and see documentation for that function for details.

## Details

Note that parameters `logitlambda`, `lnkappa`, and `lnalpha` if estimated are each estimated as having a single value that applies to all modeled variables. This differs from default behavior in **phylolm**, where these parameters only apply to the "response" and not "predictor" variables. This also differs from default behavior in **phylopath**, where a different value is estimated in each call to **phylolm** during the d-separation estimate of path coefficients. However, it is consistent with default behavior in **Rphylopars**, and estimates should be comparable in that case. These additional parameters are estimated with unbounded support, which differs somewhat from default bounded estimates in **phylolm**, although parameters should match if overriding **phylolm** defaults to use unbounded support. Finally, `phylosem` allows these three parameters to be estimated in any combination, which is expanded functionality relative to the single-option functionality in **phylolm**.

Also note that **phylopath** by default uses standardized coefficients. To achieve matching parameter estimates between **phylosem** and **phylopath**, standardize each variable to have a standard deviation of 1.0 prior to fitting with **phylosem**.

## Value

An object (list) of class 'phylosem'. Elements include:

**data** Copy of argument data

**SEM\_model** SEM model parsed from `sem` using `specifyModel` or `specifyEquations`

**obj** TMB object from `MakeADFun`

**tree** Copy of argument tree

**tmb\_inputs** The list of inputs passed to `MakeADFun`

**opt** The output from `nlminb`

**sdrep** The output from `sdreport`

**report** The output from `obj$report()`

**parhat** The output from `obj$env$parList()` containing maximum likelihood estimates and empirical Bayes predictions

## References

\*\*Introducing the package, its features, and comparison with other software (to cite when using phylosem):\*\*

Thorson, J. T., & van der Bijl, W. (In press). phylosem: A fast and simple R package for phylogenetic inference and trait imputation using phylogenetic structural equation models. *Journal of Evolutionary Biology*. doi:10.1111/jeb.14234

\*Statistical methods for phylogenetic structural equation models\*

Thorson, J. T., Maureaud, A. A., Frelat, R., Merigot, B., Bigman, J. S., Friedman, S. T., Palomares, M. L. D., Pinsky, M. L., Price, S. A., & Wainwright, P. (2023). Identifying direct and indirect associations among traits by merging phylogenetic comparative methods and structural equation models. *Methods in Ecology and Evolution*, 14(5), 1259-1275. doi:10.1111/2041210X.14076

\*Earlier development of computational methods, originally used for phlogenetic factor analysis:\*

Thorson, J. T. (2020). Predicting recruitment density dependence and intrinsic growth rate for all fishes worldwide using a data-integrated life-history model. *Fish and Fisheries*, 21(2), 237-251. doi:10.1111/faf.12427

Thorson, J. T., Munch, S. B., Cope, J. M., & Gao, J. (2017). Predicting life history parameters for all fishes worldwide. *Ecological Applications*, 27(8), 2262-2276. doi:10.1002/eap.1606

\*Earlier development of phylogenetic path analysis:\*

van der Bijl, W. (2018). phylopath: Easy phylogenetic path analysis in R. *PeerJ*, 6, e4718. doi:10.7717/peerj.4718

von Hardenberg, A., & Gonzalez-Voyer, A. (2013). Disentangling evolutionary cause-effect relationships with phylogenetic confirmatory path analysis. *Evolution; International Journal of Organic Evolution*, 67(2), 378-387. doi:10.1111/j.15585646.2012.01790.x

\*Interface involving SEM ‘arrow notation’ is repurposed from:\*

Fox, J., Nie, Z., & Byrnes, J. (2020). Sem: Structural equation models. R package version 3.1-11. <https://CRAN.R-project.org/package=sem>

\*Coercing output to phylo4d depends upon:\*

Bolker, B., Butler, M., Cowan, P., de Vienne, D., Eddelbuettel, D., Holder, M., Jombart, T., Kembel, S., Michonneau, F., & Orme, B. (2015). phylobase: Base package for phylogenetic structures and comparative data. R Package Version 0.8.0. <https://CRAN.R-project.org/package=phylobase>

\*Laplace approximation for parameter estimation depends upon:\*

Kristensen, K., Nielsen, A., Berg, C. W., Skaug, H., & Bell, B. M. (2016). TMB: Automatic differentiation and Laplace approximation. *Journal of Statistical Software*, 70(5), 1-21. doi:10.18637/jss.v070.i05

## Examples

```
# Load data set
data(rhino, rhino_tree, package="phylopath")

# Run phylosem
model = "
  DD -> RS, p1
  BM -> LS, p2
```

```

    BM -> NL, p3
    NL -> DD, p4
    "
psem = phylosem( sem = model,
                 data = rhino[,c("BM", "NL", "DD", "RS", "LS")],
                 tree = rhino_tree )

# Convert and plot using phylopath
library(phylopath)
my_fitted_DAG = as_fitted_DAG(psem)
coef_plot( my_fitted_DAG )
plot( my_fitted_DAG )

# Convert to phylo4d to extract estimated traits and Standard errors
# for all ancestors and tips in the tree.
# In this rhino example, note that species are labeled s1-s100
# and ancestral nodes are not named.
(traits_est = as_phylo4d(psem))
(traits_SE = as_phylo4d(psem, what="Std. Error"))

# Convert to sem and plot
library(sem)
my_sem = as_sem(psem)
pathDiagram( model = my_sem,
             style = "traditional",
             edge.labels = "values" )
effects( my_sem )

# Plot using semPlot
if( require(semPlot) ){
  myplot = semPlotModel( my_sem )
  semPaths( my_sem,
           nodeLabels = myplot@Vars$name )
}

```

---

phylosem\_control

*Detailed control for phylosem structure*


---

## Description

Define a list of control parameters. Note that the format of this input is likely to change more rapidly than that of [phylosem](#)

## Usage

```

phylosem_control(
  nlminb_loops = 1,
  newton_loops = 1,
  trace = 0,

```

```

    eval.max = 1000,
    iter.max = 1000,
    getsd = TRUE,
    quiet = FALSE,
    run_model = TRUE,
    getJointPrecision = FALSE
  )

```

### Arguments

nlminb_loops	Integer number of times to call <a href="#">nlminb</a> .
newton_loops	Integer number of Newton steps to do after running <a href="#">nlminb</a> .
trace	Parameter values are printed every ‘trace’ iteration for the outer optimizer. Passed to ‘control’ in <a href="#">nlminb</a> .
eval.max	Maximum number of evaluations of the objective function allowed. Passed to ‘control’ in <a href="#">nlminb</a> .
iter.max	Maximum number of iterations allowed. Passed to ‘control’ in <a href="#">nlminb</a> .
getsd	Boolean indicating whether to call <a href="#">sdreport</a>
quiet	Boolean indicating whether to run model printing messages to terminal or not;
run_model	Boolean indicating whether to estimate parameters (the default), or instead to return the model inputs and compiled TMB object without running;
getJointPrecision	whether to get the joint precision matrix. Passed to <a href="#">sdreport</a> .

### Value

An S3 object of class "phylosem\_control" that specifies detailed model settings, allowing user specification while also specifying default values

---

print.phylosem	<i>Print parameter estimates and standard errors.</i>
----------------	---

---

### Description

Print parameter estimates

### Usage

```

## S3 method for class 'phylosem'
print(x, ...)

```

### Arguments

x	Output from <a href="#">phylosem</a>
...	Not used

**Value**

prints (and invisibly returns) output from `nlminb`

---

summary.phylosem	<i>summarize phylosem</i>
------------------	---------------------------

---

**Description**

Summarize phylosem output from phylosem, including calculating intercepts at the tree root

**Usage**

```
## S3 method for class 'phylosem'
summary(object, ...)
```

**Arguments**

object	Output from <code>phylosem</code>
...	Not used

**Value**

Data-frame containing all estimated intercepts, path coefficients, and variance-covariance parameters as well as their standard errors

---

vcov.phylosem	<i>Extract Variance-Covariance Matrix</i>
---------------	---

---

**Description**

extract the covariance of fixed effects, or both fixed and random effects.

**Usage**

```
## S3 method for class 'phylosem'
vcov(object, which = c("fixed", "random", "both"), ...)
```

**Arguments**

object	output from phylosem
which	whether to extract the covariance among fixed effects, random effects, or both
...	ignored, for method compatibility

# Index

## \* data

Mlifehist\_ver1\_0, 9

as.phylo, 8, 10

as\_fitted\_DAG, 2

as\_phylo4d, 3

as\_sem, 3

average, 4

average.compare\_phylosem, 4

average\_DAGs, 4

best, 5

best.compare\_phylosem, 5

choice, 6

choice.compare\_phylosem, 6

coef.phylosem, 7

compare\_phylosem, 4–6, 7

est\_DAG, 2, 4

list\_parameters, 8

MakeADFun, 11

Mlifehist\_ver1\_0, 9

nlsminb, 11, 14, 15

parse\_path, 9

phylo4d, 3

phylosem, 2, 3, 7, 8, 10, 13–15

phylosem\_control, 8, 11, 13

print.phylosem, 14

sdreport, 11, 14

sem, 3

specifyEquations, 10, 11

specifyModel, 10, 11

summary.phylosem, 15

vcov.phylosem, 15